

MINISPLIT ON/OFF



**FUNCIÓN
TURBO**



**FLUJO DE
AIRE 3D**



**AHORRO DE
ENERGÍA**



**RECUBRIMIENTO
ANTICORROSIVO**

EFICIENCIA ESTÁNDAR

1 TON
110 v
EBDOC101A
(SOLO FRIO)
EBDOH101A
(FRIO/CALOR)

1 TON
220 v
EBDOC102A
(SOLO FRIO)
EBDOH102A
(FRIO/CALOR)

1.5 TON
220 v
EBDOC152A
(SOLO FRIO)
EBDOH152A
(FRIO/CALOR)

2 TON
220 v
EBDOC202A
(SOLO FRIO)
EBDOH202A
(FRIO/CALOR)

3 TON
220 v
EBDOC302A
(SOLO FRIO)
EBDOH302A
(FRIO/CALOR)

Capacidad (btu/h)	12000	12000	18000	24000	36000
EEER	3,60	3,52	3,55	3,51	3,58
SEER	12.2	12	12.1	12	12.2
Ahorro de Energía (%)	6	4	5	6	8
Ruido (dB)	32	32	36	46	58
Voltaje (v~)	110	220	220	220	220
Potencia (W)	1250	1260	1900	2450	3900
Refrigerante	R410A	R410A	R410A	R410A	R410A
Volumen de Aire (m3/h)	550	550	760	1100	1350
Velocidad Ventilador (rpm)	1000-1250	1000-1250	1150-1300	1150-1330	1250-1550
Consumo Modo Espera (kW/h)	0.001	0.001	0.001	0.001	0.003
Consumo Energía Plena Carga (kW/h)	0.97	0.97	1.69	2.107	3.8
Área Recomendada (m2)	12-16	12-16	17-24	25-32	33-48
Dimensiones Evaporadora (mm)	760 x 250 x 200	760 x 250 x 200	890 x 290 x 230	980 x 300 x 220	1131 x 250 x 323
Dimensiones Condensadora (mm)	730 x 240 x 490	730 x 240 x 490	760 x 260 x 550	780 x 290 x 600	833 x 317 x 700
Empaque Evaporadora (mm)	840 x 315 x 260	840 x 315 x 260	979 x 372 x 292	1096 x 390 x 297	1265 x 420 x 337
Empaque Condensadora (mm)	818 x 325 x 520	818 x 325 x 520	858 x 356 x 590	890 x 385 x 628	950 x 420 x 732
Peso Neto Evaporadora (kg)	8	8	11	14	18
Peso Neto Condensadora (kg)	29	29	35	42	61
Peso Bruto Evaporadora (mm)	10	10	13	16	22
Peso Bruto Condensadora (mm)	30	30	39	53	69